



Technical data **HSSprimus**

as of 08.2007

filter type	screen area in cm ²	heating capacity in watt	heater zones	max. pressure in bar	dimensions in mm							weight in kg
					A1/A2 (max.) ⁽¹⁾	B	C ⁽²⁾	D	E	F	G	
HSSprimus 20	10	1600	1	450	20	183	75 (4xM12)	150	590	280	260	90
HSSprimus 30	20	1600	1	350	30	183	110 (4xM16)	150	590	280	260	90
HSSprimus 45	40	1600	1	350	45	183	110 (4xM16)	150	590	280	260	100
HSSprimus 60	70	2400	1	350	60	192	120 (8xM16)	165	740	310	275	140
HSSprimus 75	110	3400	1	300	75	220	140 (8xM20)	185	730	350	290	165
HSSprimus 90	150	4000	2	300	90	230	155 (8xM20)	210	880	450	325	220
HSSprimus 110	225	5600	2	300	110	260	200 (8xM24)	245	980	480	360	310
HSSprimus 130	310	7200	2	250	130	300	220 (8xM24)	260	1195	600	400	460
HSSprimus 150	425	9500	2	250	150	330	250 (8xM30)	290	1350	750	430	700
HSSprimus 180	625	12800	2	250	180	380	295 (8xM30)	300	1750	800	450	1200

(1)= Diameter individually adjustable.

(2)= Diameter.