



Technical data **HSprimus**

as of 08.2007

filter type	screen area in cm ²	heating capacity in watt	heater zones	max. pressure in bar	dimensions in mm							weight in kg
					A1/A2 (max.) ⁽¹⁾	B	C ⁽²⁾	D	E	F	G	
HSprimus 20	5	920	1	800	20	120	75 (4xM12)	70	475	215	130	50
HSprimus 30	10	920	1	800	30	139	110 (4xM16)	120	500	215	260	50
HSprimus 45	20	1020	1	800	45	139	110 (4xM16)	120	560	290	260	60
HSprimus 60	35	1400	1	800	60	164	120 (8xM12)	130	650	300	275	75
HSprimus 75	50	2800	1	800	75	204	140 (8xM20)	155	800	305	290	120
HSprimus 90	70	3000	1	800	90	229	155 (8xM20)	160	880	390	325	170
HSprimus 110	105	4600	2	800	110	264	225 (8xM24)	200	1000	405	360	280
HSprimus 130	145	5840	2	500	130	284	245 (8xM24)	210	1050	460	380	370
HSprimus 150	195	8000	2	500	150	324,5	285 (8xM24)	250	1150	565	400	600
HSprimus 180	285	10000	2	300	180	374	295 (8xM30)	260	1400	625	420	1000
HSprimus 220	415	11200	2	250	220	450	370 (12xM30)	300	1550	685	450	1400
HSprimus 270	615	12500	2	200	270	550	455 (12xM36)	380	1800	800	520	2200
HSprimus 320	855	15600	2	200	320	600	530 (12xM36)	420	1880	870	560	3500

(1)= Diameter individually adjustable.

(2)= Diameter.