



## Technical data SF

as of 08.2007

filter type	active screen area	heating capacity in watt		heater zones		pressure <sup>(1)</sup> in bar max.	temp. <sup>(2)</sup> in °C max.	Q <sup>(3)</sup> in kg/h	dimensions in mm									weight in kg	
		electric	oil/ vapor	electric	oil/ vapor				A	B	C	D	E	F	G	H	I <sup>(4)</sup>		K
SF 30	8	1200	1870	2	2	500	320	40	460	154	-	250	90	200	95	93	15	90	30
SF 45	19	1900	2730	2	2	500	320	120	560	210	-	335	130	250	138	112	20	120	75
SF 60	35	2240	3690	2	2	500	320	220	670	270	-	420	150	310	172	112	20	140	115
SF 75	45	5860	8580	2	2	500	320	310	720	290	-	440	170	350	225	112	25	175	220
SF 90	70	7300	10140	2	2	350	320	550	900	395	20	580	220	440	319	122	30	220	460
SF 130	135	8000	10760	2	2	350	320	910	950	432	20	630	245	470	352	122	30	220	530
SF 150	180	8000	10760	2	2	350	320	1430	950	432	20	630	245	470	352	122	35	220	550
SF 175	250	12000	16380	3	2	350	320	2080	1100	550	20	940	305	580	400	162	40	310	1200
SF 200	320	-	28000	-	2	300	320	2850	1200	635	20	1150	360	680	445	175	45	320	1680
SF 250	500	-	32000	-	2	250	320	4070	1300	690	20	1170	400	685	545	125	50	370	2300

(1)= High pressure versions available as an option.

(2)= Up to 400°C possible as an option.

(3)= Based on: MFI 2-5, filtration fineness 200 µm and differential pressure 50 bar.

(4)= The dimension "I" can be freely chosen, the values given are minimum values.