



## Technical data **SFXmagnus**

as of 08.2007

filter type	active screen area		heating capacity in watt		heater zones		pressure <sup>(1)</sup> in bar max.	temp. <sup>(2)</sup> in °C max.	Q <sup>(3)</sup> in kg/h	dimensions in mm								weight in kg
	total in cm <sup>2</sup>	direct in cm <sup>2</sup>	electric	oil/vapor	electric	oil/vapor				A	B	C	D	E	F	G	H <sup>(4)</sup>	
SFXmagnus 45	250	90	7200	8500	3	2	350	320	400	800	300	700	680	190	110	205	20	250
SFXmagnus 60	450	160	8500	10000	3	2	350	320	700	830	360	730	780	220	125	208	20	350
SFXmagnus 75	600	220	8700	10000	3	2	350	320	900	880	390	780	860	230	140	252	25	450
SFXmagnus 90	1000	350	18500	22000	3	2	300	320	1000	1100	500	1000	960	280	160	328	30	800
SFXmagnus 130	1400	500	19000	25000	3	2	300	320	2000	1150	530	1050	900	300	175	362	30	950
SFXmagnus 150	1600	600	19500	25000	3	2	300	320	2500	1200	550	1100	1000	320	175	365	35	1050
SFXmagnus 175	2200	1000	23000	32000	4	2	250	320	3500	1300	650	1300	1050	380	250	408	40	1700
SFXmagnus 200	3100	1400	32000	36000	4	2	200	320	5000	1300	750	1300	1350	450	270	555	45	3000
SFXmagnus 250	4000	1800	-	40000	-	2	200	320	7800	1400	800	1400	1500	500	320	555	50	3500
SFXmagnus 330	6400	2900	-	45000	-	2	200	320	12000	1700	950	1700	1550	550	350	700	55	4000
SFXmagnus 400	8700	3800	-	60000	-	2	200	320	16000	1800	1100	1800	1600	650	400	800	60	7000
SFXmagnus-D 330	12800	5800	-	60000	-	3	200	320	24000	1800	950	1700	1600	550	350	1100	55	8000
SFXmagnus-D 400	17400	7600	-	80000	-	3	200	320	32000	1900	1100	1800	1700	650	400	1400	60	12000

(1)= High pressure versions available as an option.

(2)= Up to 400 °C possible as an option.

(3)= Based on: 1000 Pas, 60 µm and Δp 40 bar.

(4)= The dimension "H" can be freely chosen, the values given are minimum values.